



### MATERIALS AND FINISH

L : STEEL MATERIAL, TIN FINISHED  
 CONNECTOR INSULATOR : PBT THERMOPLASTIC,  
 30% GLASS FILLED, UL 94V-0 RATED, BLACK COLOR  
 COAXIAL INSULATOR : TEFLON UL 94V-0 WHITE COLOR  
 SIGNAL CONTACT MATERIAL: BRASS, FULL GOLD FLASH  
 COAXIAL CONTACT MATERIAL: BRASS, 15u" GOLD PLATED

### ELECTRICAL CHARACTERISTICS

SIGNAL CONTACT CURRENT RATING : 3.0 AMPS  
 SIGNAL CONTACT RESISTANCE : 10 MILLIOHMS MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE :  
 1000 V AC FOR 1 MINUTE  
 INSULATION RESISTANCE : 5000 MEGAOHMS MIN.  
 TEMPERATURE RATING : -55°C ~ +125°C  
 COAXIAL CONTACT IMPEDANCE: 75 OHMS

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PJECTION

照片框

ORDER INFORMATION

DXS-S75-21W4-LF  
 SERIES | LEADFREE  
 | 21W4  
 | 75 OHM  
 FEMALE

DESCRIPTION: D-SUB CONNECTOR (coaxial Contact Straight Solder Machined Pin)