



RECOMMENDED PCB LAYOUT

MATERIAL
 INSULATOR: GLASS-REINFORCED THERMOPLASTIC (PBT),
 UL94V-0 RATED.
 CONTACT: COPPER ALLOY.
 PLATING: CONTACT AREA- SELECT GOLD PLATED OVER NICKEL.
 SOLDER AREA- TIN OVER NICKEL.

ELECTRICAL
 DIELECTRIC WITHSTANDING VOLTAGE: 1,000 VAC RMS.
 CURRENT RATING: 3 AMP.
 INSULATION RESISTANCE: 5,000 MEG. OHMS MIN. AT 500 VDC.
 CONTACT RESISTANCE: 20 MILLI OHMS MAX.

MECHANICAL
 INSERTION FORCE: 340 GRAMS MAX PER CONTACT PAIR.
 WITHDRAWAL FORCE: 28 GRAMS MIN PER CONTACT PAIR.

ENVIRONMENTAL
 TEMPERATURE RANGE: -55° TO +85°.



DETAIL OF KINKED

△ KINKED POSITION ARE #A3, #A29,
 AND #B3, #B29,

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PJECTION

10-30 ±0.3

100-300 ±0.5

ANGULAR ±0.5°

照片框

ORDER INFORMATION

E-DK-062-LF
 SERIES | LEADFREE
 | 62 WAY
 | KINK
 | DIP 180°

DESCRIPTION: CARDEDGE SLOT 62 P, 2.54mm PITCH