



P.C.B.Layout

MATERIALS

- * Body : Black Liquid Crystal Polstal (L.C.P.) UL (94V-0)
- * Contact : Copper alloy
- * Contact plated : Au over niket ,Ped tin plating

SPECIFICATION

- * Contact curret rating : 1 AMP
- * Conact resistance : 30 Milli OHMS Max.
- * Insulation resistance : 5000 megoohms Min. initial
- * Operating temperature : -55°C to +125°C
- * Dielectric Withstanding Voltage : AC 200V
- * Capacitance : 1pf Max.
- * Durability : 25 cycle Min.
- * Conact force : Low mating force

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ± 0.50

.X, ± 0.35

.XX, ± 0.25

.XXX, ± 0.05

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

E08-VP-xxx-LF
SERIES LEADFREE
020.040.060.070 WAY
POST
180°SMT

DESCRIPTION: 0.8mm Card Edge Connector XXP SMD type