



P.C.B.Layout

MATERIALS

- * Body : Black Liquid Crystal Polstal (L.C.P.) UL (94V-0)
- * Contact : Copper alloy
- * Contact plated : Au over niket ,Ped tin plating

SPECIFICATION

- * Contact current rating : 1 AMP
- * Contact resistance : 30 Milli OHMS Max.
- * Insulation resistance : 5000 megohms Min. initial
- * Operating temperature : -55°C to +125°C
- * Dielectric Withstanding Voltage : AC 200V
- * Capacitance : 1pf Max.
- * Durability : 25 cycle Min.
- * Contact force : Low mating force

Contact	Dim_A	Dim_A Contact/2
80P	16.80	22P
90P	18.40	24P
100P	20.80	27P
120P	24.80	32P
140P	28.80	37P
160P	24.80	32P

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ± 0.50

.X ± 0.35

.XX ± 0.25

.XXX ± 0.05

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

E08-VPC-xxx-LF
SERIES | | LEADFREE
| | 080~160 WAY
| CAP
| POST
180°SMT

DESCRIPTION: 0.8mm Card Edge Connector XXXP SMD type