


PCB LAYOUT

Note:

- 1:Electical Performance
 - 1.1.Dielectric Withstanding Voltabge: 500V/AC For 1.0 Minute.
 - 1.2.Contadt Resistance:30mΩ Max
 - 1.3.linsulation Resistance:1000MΩ Min
- 2.Mechanical Performance.
 - 2.1.CONTACT INSERTION FORCE: 0.115Kg Max Per.Contact Pair.
 - 2.2.CONTACT WITHDRAWAL FORCE: 0.015Kg Min Per.Contact Pair.
 - 2.3.Terminal Retention Force (in housing): 0.5Kg Minper Terminal.
- 3.Material & Finish:
 - 3.1.Insulator:Hi-Temp PPS UL 94V-0,260'/10Sec, Black
 - 3.2.Contact Plating: Tin Plating At Solder Tail Area;
Gold Plating At Mating Area, All Over Nickel Plating.
- 4.Environmental:Operating Temperature: -55°C~+85°C



SECTION: A-A

RoHS Compliant

TOLERANCES ARE

DRAWING BY CY

X. ± 0.30

CHECKED BY GENIUS

.X ± 0.20

UNIT / mm

SCALE 1 : 1

.XX ± 0.10

DATE

.XXX ± 0.01

ANG ± 1°

SIZE A4

PPOJECTION

照片框

ORDER INFORMATION

E10-VPC-016-LF
 SERIES T T LEADFREE
 16 WAY
 CAP
 POST
 180°SMT

DESCRIPTION: PCI PH:1.0 SMT 成品

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com