



RECOMMENDED P.C.B LAYOUT

SPECIFICATIONS

CURRENT RATING: 3 AMP

INSULATION RESISTANCE: 1000M OHMS MIN.

DIELECTRIC WITHSTANDING: 600V AC/DC

CONTACT RESISTANCE: 20m OHMS MAX.

OPERATING TEMPERATURE: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$

MATERIALS

CONTACT MATERIAL: PHOSPHOR BRONZE

INSULATION MATERIAL: POLYESTER, UL 94V-0

NYLON 6T (BLACK)

RoHS Compliant

TOLERANCES ARE

DRAWING BY CY

 $X_{\pm}$

CHECKED BY GENIUS

$$X \pm 0.30$$

UNIT / mm

.XXX ± 0.10

DATE _____

	ANG ±
--	-------

SIZE A4

PJECTION 

照片框

ORDER INFORMATION

F-V75PC-2Xxx-LF

SERIES

SERIES

LEADFREE

2X03:06 WAY

2X40:80 WAY

180°SMT

CAF

| POST
HIGH 3.5mm

HIGH 7.5mm

DESCRIPTION: 2.54mm Female Socket Dual Row SMD type (H=7.5)

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com