



Recommended P.C.B Layout

## MATERIAL

Contact Pin : Phosphor Bronze

## SPECIFICATION

Current Rate : 3 AMP

Insulation Resistance : 5000MΩMin.

Contact Resistance : 20mΩMax.

Dielectric Voltage : AC 500V for one minute

POLES	DIM E	POLES	DIM E
		21	50.80
2	2.54	22	53.34
3	5.08	23	55.88
4	7.62	24	58.42
5	10.16	25	60.96
6	12.70	26	63.50
7	15.24	27	66.04
8	17.78	28	68.58
9	20.32	29	71.12
10	22.86	30	73.66
11	25.40	31	76.20
12	27.94	32	78.74
13	30.48	33	81.28
14	33.02	34	83.82
15	35.56	35	86.36
16	38.10	36	88.90
17	40.64	37	91.44
18	43.18	38	93.98
19	45.72	39	96.52
20	48.26	40	99.06

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ± 3°

P PROJECTION

照片框

ORDER INFORMATION

F-WX-2Xxx-LF  
SERIES | LEADFREE  
2X02:04WAY  
2X40:80WAY  
NON POST  
90°SMT

DESCRIPTION: FEMALE HEADER 2.54\*2.54mm  
HORIZONTAL PIN, DUAL ROWS HEIGHT 8.5mm Tube

煜倫股份有限公司

www.morethanall.com