

Specifications

Current Rating: 1Amp

Insulation Resistance: 1000MΩ Min

Dielectric Withstanding Voltage: 300VAC

Contact Resistance: 20mΩ Max.

Operating Temperature: -40°C to +105°C

Max Process Temp: 230°C for 30~60 sec.

Materials

Contact Material: Phosphor Bronze

Insulator Material: High Temperature


Thermoplastic, UL 94V-0 LCP

or the equivalent material

Recommended P.C.Board

Layout

(Tolerance: ±0.05)



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ± 0.30

.X, ± 0.25

.XX, ± 0.15

.XXX, ± 0.10

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

F10-WXC-1Xxx-LF
SERIES LEADFREE
1X02:02WAY
90°SMT MYLAR
NON POST
1X40:40WAY

DESCRIPTION: 1.00 FEMALE HEADER SINGLE ROW SMT TYPE