



$\phi 1.09 - \phi 1.04$  Dia of finished hole after plating  
 Drilled hole Dia.  $\phi 1.17 - \% 1.13$   
 Tin/Lead plated 0.005 Min.  
 Copper plating 0.025-0.075  
 (Follow SPEC. -PC-104)

Recommend P.C.B. Layout

TOP View

**SPECIFICATIONS**  
 CURRENT RATING: 3 AMPS  
 INSULATOR RESISTANCE: 5000 MEGPHMS MIN.  
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.  
 DIELECTRIC WITHSTANDING: AC 500V  
 OPERATING TEMPERATURE:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

**MATERIAL**  
 CONTACT: PHOSPHOR BRONZE (GOLD FLUSH)  
 INSULATOR: PA-9T, UL 94V-0

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X.  $\pm 0.50$   
 .X  $\pm 0.35$   
 .XX  $\pm 0.25$   
 .XXX  $\pm 0.05$   
 ANG  $\pm$

PJECTION

照片框

ORDER INFORMATION

FE-D114121-2X32-LF  
 SERIES | | | LEADFREE  
 | | | 64WAY  
 | | | DIP 12.19mm  
 | | | HIGH 11.40mm  
 | | | DIP 180°

DESCRIPTION: