



Electrical Properties

- 1.100% Test(Open Short Miss Wire)
- 2.Contact Resistance:3Ω Maximum
- 3.Insulation Resistance:5MΩ Minimum
- 4.Hi-Pot: 300V 10ms

P1	Drain	P2
4	Black	5
2	White	3
1	Green	2
<u>PIN OUT</u>		

7	H.S. TUBE	∅0.8mm L=20mm Color:Black	2PCS	.
6	H.S. TUBE	∅5.0mm L=20mm Color:Black	2PCS	.
5	CABLE	UL2464 28AWGx3C+AEB OD=3.8mm Color:Black	1PCS	.
4	TERMINAL	2.54mm Copper, Tin Plated PVK-T-22	3PCS	.
3	HOUSING	2.54mm 2x5Pin Thermoplastic Color:Black PVK-H-2X05	1PCS	.
2	TERMINAL	1.25mm Phosphor Bronze,Tin Plated FH-T-28	3PCS	.
1	HOUSING	1.25mm 4Pin Nylon66 UL94V-0 Color:White FH-H-04	1PCS	.
ITEM	PARTS NAME	SPECIFICATION STANDARD	Q'TY	REMARK
MATERIAL LIST				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY		X. ± .X ± 0.35 .XX ± 0.25 .XXX ± 0.15 ANG ±
CHECKED BY GENIUS		
UNIT / mm	SCALE 1 : 1	
DATE		
SIZE A4	PPOJECTION	

照片框

ORDER INFORMATION

FHPVK-04100328R1AEB-F37C-LF									
SERIES		LEADFREE		370mm		FEMALE TO FEMALE		BRAID	
04 TO 10P3C WAY		28 AWG		EARTH WIRE		AL.(ALUMINUM FOIL)		ROUND CABLE	

DESCRIPTION: Cable 1.25mm 4Pin To 2.54mm 2x5Pin UL2464#28x3C+AEB L=370mm OD:3.8 Black