

**Electrical Properties**

1. 100% Test (Open Short Miss Wire)
2. Contact Resistance: 3Ω Maximum
3. Insulation Resistance: 5MΩ Minimum
4. Hi-Pot: 300V 10ms

P1	Drain	P2
4	Black	1
2	White	10
1	Red	6
△ XA PIN OUT		

ITEM	PARTS NAME	SPECIFICATION	STANDARD	Q'TY	REMARK
7	H.S. TUBE	∅5.0mm L=20mm Color:Black		2PCS	.
6	H.S. TUBE	∅0.8mm L=20mm Color:Black		2PCS	.
5	CABLE	UL2464 28AWGx3C+AEB OD=3.5mm Color:Black		1PCS	.
4	TERMINAL	2.54mm Copper, Tin Plated		3PCS	.
3	HOUSING	2.54mm 2x5Pin Thermoplastic Color:Black		1PCS	.
2	TERMINAL	1.25mm Phosphor Bronze, Tin Plated		3PCS	.
1	HOUSING	1.25mm 4Pin Nylon66 UL94V-0 Color:White		1PCS	.

**RoHS Compliant**

TOLERANCES ARE



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±  
.X ± 0.35  
.XX ± 0.25  
.XXX ± 0.15  
ANG ±



**ORDER INFORMATION**

FHPVK-04100328R1AEB-F43C-LF

SERIES | 04 TO 10P3C WAY | 28 AWG | BRAID | EARTH WIRE | AL.(ALUMINUM FOIL) | ROUND CABLE | 430mm | LEADFREE | FEMALE TO FEMALE

DESCRIPTION: Cable 1.25mm 4Pin To 2.54mm 2x5Pin UL2464#28x3C+AEB L=430mm OD:3.8 Black