

Electrical Properties

- 1.100% Test(Open Short Miss Wire)
- 2.Contact Resistance: 3Ω Maximum
- 3.Insulation Resistance: 5MΩ Minimum
- 4.Hi-Pot: 300V 10ms

P1	Drain	P2
4	Black	8
3	Green	6
2	White	4
1	Red	2
	<u>PIN OUT</u>	

7	H.S. TUBE	∅0.8mm L=20mm Color:Black	2PCS	.
6	H.S. TUBE	∅5.0mm L=20mm Color:Black	2PCS	.
5	CABLE	UL2464 28AWGx4C+AEB OD=4.0mm Color:Black	1PCS	.
4	TERMINAL	2.54mm Copper, Tin Plated PVK-T-22	4PCS	.
3	HOUSING	2.54mm 2x5Pin Thermoplastic Color:Black PVK-H-2X05	1PCS	.
2	TERMINAL	1.25mm Phosphor Bronze,Tin Plated FH-T-28	4PCS	.
1	HOUSING	1.25mm 4Pin Nylon66 UL94V-0 Color:White FH-H-04	1PCS	.
ITEM	PARTS NAME	SPECIFICATION STANDARD	Q'TY	REMARK
MATERIAL LIST				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X. ±

CHECKED BY GENIUS

.X ± 0.35

UNIT / mm

SCALE 1 : 1

.XX ± 0.25


DATE

.XXX ± 0.15

ANG ±

SIZE A4

PPOJECTION



ORDER INFORMATION

FHPVK-041028R1AEB-F70C-LF

SERIES

04 TO 10P4C WAY

28 AWG

ROUND CABLE

370mm

BRAID

EARTH WIRE

AL.(ALUMINUM FOIL)

LEADFREE

FEMALE TO FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: Cable 1.25mm 4Pin To 2.54mm 2x5Pin UL2464#28x4C+AEB L=700mm OD:4.0 Black