



P1	1	WHITE	1	P2
	2	WHITE	2	

WIRING TABLE

Electronics Test :

1. Contact Resistance : 2 Ω Max.
2. 100% open & short test (set at 20 K Ω)
3. At DC = 300V , Insulation Resistance : 20 M Ω Min.
4. Test Condition : Temperature : 25 $\pm$ 5 $^{\circ}$ C , Humidity : 50% RH Max.

3	50079-8000/Molex	SOCKET CONTACT	4 PCS
2	51021-0200/Molex	HOUSING, 2-POS., 1.25mm PITCH, WHITE	2 PCS
1	Spec./Rei Hsing	WIRE, 26 AWG, UL 10368, HALOGEN FREE	A/R
ITEM	PART NO./SUPPLIER	DESCRIPTION	Q'TY

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. $\pm$
.X $\pm$
.XX $\pm$
.XXX $\pm$
ANG $\pm$

照片框

ORDER INFORMATION

FHX2-020226MX-F7C-HF

SERIES

26 AWG

MOLEX

70mm

02 TO 02 WAY

HALOGEN FREE

FEMALE TO FEMALE

DESCRIPTION: WIRE HARNESS ASSEMBLY