

WIRING CHART

A	顏色	B
1	RED	1
2	RED	2
3	BLACK	3
4	BLACK	4
5	BLUE	5
6	WHITE	6
7	BLACK	7
8	BLUE	8
9	WHITE	9
10	BLACK	10
11	BLUE	11
12	WHITE	12
13	BLACK	13
14	BLUE	14
15	WHITE	15
16	BLACK	16
17	BLACK	18
18	BLACK	17

NOTES:

1. ALL DIMENSIONS ARE "mm".
2. THE PRODUCT MUST BE COMPLY WITH THE DIRECTIVE OF ROHS.

ELECTRICAL TESTING:

1. 100% OPEN/SHORT TEST
2. CONTACT RESISTANCE: 5mΩ
3. INSULATION RESISTANCE: 5MΩ Min

NO.	ITEM.	DESCRIPTION	Q'TY	UL/CSA No.
1	WIRE:	UL1571 #28 OD:0.6 RED	2PCS	E108485
2	WIRE:	UL1571 #28 OD:0.6 BLACK	8PCS	E108485
3	WIRE:	UL1571 #28 OD:0.6 BLUE	4PCS	E108485
4	WIRE:	UL1571 #28 OD:0.6 WHITE	4PCS	E108485
5	HOUSING:	FI-H-20	2PCS	E186792
6	TERMINAL:	FI-T-28	36PCS	
7	NYLON BRAID:	7φ*L:100 BLACK	1PCS	
8	ACETATE TAPE :	W:20*L:20	2PCS	
9				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

PJECTION



ORDER INFORMATION

FIX2-202028-F15C5-LF

SERIES

LEADFREE

155mm

FEMALE TO FEMALE

28 AWG

20 TO 20 WAY

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: CABLE ASS'Y