




Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	22
P	Pitch(间距)	1.0±0.10
TP	Total Pitch(总间距)	21±0.15
W	Width(总宽度)	23±0.15
M	Margin(边缘宽度)	1.0±0.15
L	Total Length(总长度)	478±1.0
T	Insertion Thickness(插入厚度)	0.303±0.05
ST	FFC Body Thickness(线身厚度)	0.121±0.03
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1.0
B1/B2	Supporting tape Length(补强板长度)	6/6±2.0
Cw	Conductor Width(导体宽度)	0.65±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

ELECTRICAL CHARACTERISTICS
Conductor Resistance: JISC-3102(at20℃) 2.20Ω/M Max.
Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.
Dielectric Strength: Apply AC 500V for one minute.
Continuity Test: Apply microtest machine No Open/Short
Rated voltage & temperature:UL20798 60V 80℃

包装方式: 线材每50PCS两端用纸带包好,10把装1PE袋(需整齐排好),
然后把装好1PE袋的产品用纸板固定好,10袋装一纸箱.
批量不够5000PCS可自行选择合适纸箱

Material
Insulation: Flame Retardant Polyeste
Color: White
Conductor: Copper with 1u m min.tin-Plating
Supporting Tape: Flame Retardant Polyester
Color: Blue

包材	纸箱 K=A 11.6"*9.6"*9.6" 环保RoHS	1/5000	PCS	GC01
	PE袋10.5"*13.5" 有环保标示 环保RoHS	1/500	PCS	XHSL
	纸板A=A 13.2"*9.8"环保RoHS	1/500	PCS	GC01
	纸带 15*0.1"环保RoHS	0.000006	Kg	HY08
4	FFC-ST-0.225*12环保ROHS	W=23	mm	LR00
3	FFC-CN-0.035*0.65 环保ROHS	2.12923	g	MX00
2	FFC-FD-0.043*120 环保ROHS	W=23 L=478	mm	XSD0
1	FFC-FM-0.043*120 B-NS 环保ROHS	W=23 L=470	mm	XSD0
序号	品 名/规 格	用量	单位	代码

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

FPA-CA22-478-LF

SERIES
LEADFREE
478mm
22WAY
SAME SIDE
CABLE

DESCRIPTION: