



FPC/FFC Insert Direction
Recommended P.C.B Layout

SPEC :

- Housing: High-Temp Plastic, UL94-V
Color: Nature (Ivory) (LCP)
- Locker: High-Temp Plastic, UL94-V
Color: Black (LCP)
- Contact: Phosphor Bronze (C5191)
Initial: 30m Ohms Max.
Voltage Rating: 50V AC, DC
- Solder Tab: BRASS (C2680)
- Temperature Rating: -25°C ~ +85°C
- Dielectric Withstanding Voltage: 500V AC/Min

No. of contacts	Dimensions			
	A	B	C	D
4	8.90	3.00	8.50	5.10
5	9.90	4.00	9.50	6.10
6	10.90	5.00	10.50	7.10
7	11.90	6.00	11.50	8.10
8	12.90	7.00	12.50	9.10
9	13.90	8.00	13.50	10.10
10	14.90	9.00	14.50	11.10
11	15.90	10.00	15.50	12.10
12	16.90	11.00	16.50	13.10
13	17.90	12.00	17.50	14.10
14	18.90	13.00	18.50	15.10
15	19.90	14.00	19.50	16.10
16	20.90	15.00	20.50	17.10
17	21.90	16.00	21.50	18.10
18	22.90	17.00	22.50	19.10
19	23.90	18.00	23.50	20.10
20	24.90	19.00	24.50	21.10
21	25.90	20.00	25.50	22.10
22	26.90	21.00	26.50	23.10
23	27.90	22.00	27.50	24.10
24	28.90	23.00	28.50	25.10
25	29.90	24.00	29.50	26.10
26	30.90	25.00	30.50	27.10
27	31.90	26.00	31.50	28.10
28	32.90	27.00	32.50	29.10
29	33.90	28.00	33.50	30.10
30	34.90	29.00	34.50	31.10
N	N+4.90	N-1.00	N+4.50	N+1.10

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

PJECTION

照片框

ORDER INFORMATION

FPA-WHB20-xx-LF
SERIES | | | LEADFREE
04~30WAY
HIGH 2.06mm
90°SMT | | | BOTTOM CONTACT
HINGED ZIF

DESCRIPTION: 1.0PH 2.0H 掀蓋臥貼前插

煜倫股份有限公司

www.morethanall.com