




Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	8
P	Pitch(间距)	0.50±0.05
TP	Total Pitch(总间距)	3.5±0.1
W	Width(总宽度)	4.5±0.1
M	Margin(边缘宽度)	0.5±0.1
L	Total Length(总长度)	320±5
T	Insertion Thickness(插入厚度)	0.318±0.050
ST	FFC Body Thickness(线身厚度)	0.136±0.030
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1
B1/B2	Supporting tape Length(补强板长度)	6/6±2
Cw	Conductor Width(导体宽度)	0.32±0.03
Ct	Conductor Thickness(导体厚度)	0.050±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

ELECTRICAL CHARACTERISTICS

Conductor Resistance: JISC-3102(at20℃) 2.20Ω/M Max.

Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.

Dielectric Strength: Apply AC 500V for one minute.

Continuity Test: Apply microtest machine No Open/Short

Rated voltage & temperature:UL20624 60V 80℃

Material

Insulation: Flame Retardant Polyeste

Color: White

Conductor: Copper with 1u m min.tin-Plating

Supporting Tape: Flame Retardant Polyester

Color: Blue

4	FFC-ST-0.225*12 环保ROHS	4.5	mm
3	FFC-CN-0.050*0.32 环保ROHS	0.3641344	g
2	FFC-FD-0.043*120 环保ROHS	W=4.5 L=320	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=4.5 L=312	mm
序号	品名/规格	用量	单位

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

FPV-CA08-320-LF
SERIES | LEADFREE
08 WAY
SAME SIDE
CABLE

DESCRIPTION: