


FFC CABLE Charateristics特性表

UL STYLE: 20798

	Test Item 測試項目	Testing Method 測試方法	Specification 規格
1	Conductor resistance導體阻抗	JIS-C-3102(at20°C)	2.2 Ω/M MAX.
2	Insulation resistance絕緣阻抗	Apply the voltage of DC 500V for min	More than 1000MΩ 大於1000MΩ
3	Dielectric Srtength耐壓強度	AC 500V, 0.5Ma, 1分鐘,相鄰兩導體在空氣中	PASS
4	Continuity Test導通測試	Apply Test DC 3V	No open/Short Citcuit
5	Rated Current 額定電流		0.5A
6	Rated Voltage&Temperature 額定電壓及溫度	UL Sub, 758	60V 80°C
7	Operating Temperature操作溫度	Fixed Wiring Condition	-40°C~80°C
8	Flammability Test耐燃性測試	UL Sub, 758 V W-1	PASS
9	Heat Resistance抗熱測試	85°C / 96Hrs	No Trouble with insulation Resistance and withstand voltage絕緣電阻與耐電壓符合要求
10	Humidity Resistance抗溼測試	40°C , 95%RH, 96Hrs	
11	Temperature Cycling Test 溫度循環測試	-40°C for 4hrs--85°C for 4hrs--25°C for 1hrs (5 cyc)	
12	Sliding Test柔性測試	R=Cable thickness	耐曲折測試≥30cycle
13		15mmR,70cycle/min , 20mm往復運動	耐曲折測試≥100,000cycle
14	Abrasion Test耐磨測試	Ø5mm,600g,60cycle/min	Min 10,000cycles 10,000回以上



SYMBOL	N	P	W	SP	M	A	TL	T	S1	S2	S3	S4
RANGE	40	0.5	20.5	19.5	0.5	0.0	20.0	0.3	4.0	4.0	6.0	6.0
TOLERANCE		±0.05	±0.1	±0.1	±0.1	<0.5	±2.0	±0.05	±1.0	±1.0	±2.0	±2.0
CONDUCTOR			TIN PLATED COPPER WIRE (TIN 1~3um)			THICKNESS(Ct)			0.035		±0.005	
SPECIFICATION						WIDTH(Cw)			0.3		±0.03	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

FPV-CA40-020-LF

SERIES

LEADFREE

20mm

40 WAY

SAME SIDE

CABLE

DESCRIPTION: