



Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	40
P	Pitch(间距)	0.50±0.05
TP	Total Pitch(总间距)	19.5±0.2
W	Width(总宽度)	20.5±0.2
M	Margin(边缘宽度)	0.50±0.10
L	Total Length(总长度)	50±3
T	Insertion Thickness(插入厚度)	0.303±0.050
ST	FFC Body Thickness(线身厚度)	0.121±0.030
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1
B1/B2	Supporting tape Length(补强板长度)	6/6±2
Cw	Conductor Width(导体宽度)	0.32±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.225±0.005
A1	Slanting(线口倾斜度)	<0.5

ELECTRICAL CHARACTERISTICS

Conductor Resistance: JISC-3102(at20°C) 2.20Ω/M Max.
 Insulation Resistance: Apply the voltage of DC 500V for one minute 100MΩ Min.
 Dielectric Strength: Apply AC 500V for one minute.
 Continuity Test: Apply microtest machine No Open/Short
 Rated voltage & temperature:UL20624 60V 80°C

WX-523/WWYY
 YY表示年,如:2016年,那么此处就填就填"16"
 WW表示第几周,如:
 当天出货日期是37
 周,那么此处就填 "37"

Material
 Insulation: Flame Retardant Polyeste
 Color: White
 Conductor: Copper with lu m min.tin-Plating
 Supporting Tape: Flame Retardant Polyester
 Color: Blue

贴标签方式: 每条FFC在无印字面居中贴标签并用透明胶纸缠绕一圈, 标签内容如图。
 包装方式: 线材每50PCS两端用纸带包好,28把装1PE袋(需整齐排好),
 然后把装好1PE袋的产品用纸板固定好,10袋装一纸箱。
 批量不够14000PCS可自行选择合适纸箱

包材	纸箱 K=K 11.6"*9.6"*9.6" 环保ROHS	1/14000	PCS
	PE袋10.5"*13.5" 有环保标示 环保ROHS	1/1400	PCS
	纸板A=A 13.2"*9.8"环保ROHS	1/1400	PCS
	纸带 15*0.1"环保ROHS	0.000006	Kg
4	FFC-ST-0.225*12 环保ROHS	20.5	mm
3	FFC-CN-0.035*0.32 环保ROHS	0.1991	g
2	FFC-FD-0.043*120 环保ROHS	W=20.5 L=50	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=20.5 L=42	mm
序号	品名/规格	用量	单位

RoHS Compliant



煜倫股份有限公司

www.morethanall.com

DRAWING BY CY
 CHECKED BY GENIUS
 UNIT/mm SCALE 1:1
 DATE
 SIZE A4 PPROJECTION

TOLERANCES ARE

X.±
 .X±
 .XX±
 .XXX±
 ANG ±

照片框

ORDER INFORMATION

FPV-CA40-050-LF
 SERIES LEADFREE
 50mm
 40 WAY
 SAME SIDES
 CABLE

DESCRIPTION: