




Symbol 标号	Item 项目	Specification 规格
N	No. of Conductors(导体芯数)	50
P	Pitch(间距)	0.5±0.05
TP	Total Pitch(总间距)	24.5±0.10
W	Width(总宽度)	25.5±0.10
M	Margin(边缘宽度)	0.5±0.10
L	Total Length(总长度)	30±2
T	Insertion Thickness(插入厚度)	0.328±0.05
ST	FFC Body Thickness(线身厚度)	0.121±0.03
S1/S2	Conductor Strip Length(裸铜长度)	4/4±1
B1/B2	Supporting tape Length(补强板长度)	6/6±2
Cw	Conductor Width(导体宽度)	0.32±0.03
Ct	Conductor Thickness(导体厚度)	0.035±0.005
Ft	Insulation Film Thickness(绝缘膜厚度)	0.043±0.005
Bt	Supporting tape Thickness(补强板厚度)	0.250±0.005
A1	Slanting(线口倾斜度)	<0.5

ELECTRICAL CHARACTERISTICS

Conductor Resistance: JISC-3102(at20℃) 2.20Ω/M Max.
Insulation Resistance: Apply the voltage of DC 500V
for one minute 100MΩ Min.
Dielectric Strength: Apply AC 500V for one minute.
Continuity Test: Apply microtest machine No Open/Short
Rated voltage & temperature:UL20624 60V 80℃

Material

Insulation: Flame Retardant Polyeste
Color: White
Conductor: Copper with 1u m min.tin-Plating
Supporting Tape: Flame Retardant Polyester
Color: Blue

包装方式:线材每50PCS中间用纸带包好, 30把装1PE袋(需整齐排好),
然后把装好1PE袋的产品用纸板固定好, 10把装一纸箱.
批量不够15000PCS可自行选择合适纸箱

包材	纸箱 K=K 11.6"*9.6"*9.6" 环保ROHS	1/15000	PCS
	PE袋10.5"*13.5" 有环保标示 环保ROHS	1/1500	PCS
	纸板A=A 13.2"*9.8" 环保ROHS	1/1500	PCS
	纸带 15*0.1" 环保ROHS	0.1	Kg
4	FFC-ST-0.250*12 环保ROHS	25.5	mm
3	FFC-CN-0.035*0.32 环保ROHS	0.149352	g
2	FFC-FD-0.043*120 环保ROHS	W=25.5 L=30	mm
1	FFC-FM-0.043*120 G-NS 环保ROHS	W=25.5 L=22	mm
序号	品名/规格	用量	单位

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X.±
.X±
.XX±
.XXX±
ANG±

照片框

ORDER INFORMATION

FPV-CA50-030-LF
SERIES | LEADFREE
| 30mm
| 50 WAY
| SAME SIDE
CABLE

DESCRIPTION: