




SYMBOL	N	P	W	SP	M	A	TL	T	S1	S2	S3	S4
RANGE	12	0.5	6.5	5.5	0.5	0	51	0.30	4.0	4.0	8.0	8.0
TOLERANCE		±0.05	±0.08	±0.08	±0.08	<0.5	±2.0	±0.05	±1.0	±1.0	±1.5	±1.5
Insulation / 膠膜			UL20706 White t=0.06 / White t=0.06			Conductor / Plating 導體 / 鍍層		CT 0.05±0.005		TIN PLATED COPPER WIRE (TIN 1~3um)		
Suppoort Tape / 補強板			Blue t=0.200					CW 0.3±0.03				

FFC CABLE Charateristics特性表 UL STYLE: 20706

	Test Item 測試項目	Testing Method 測試方法	Specification 規格
1	Conductor resistance導體阻抗	JIS-C-3102(at20℃)	1.42 Ω/M MAX.
2	Insulation resistance絕緣阻抗	Apply the voltage of DC 500V for min	More than 1000MΩ 大於1000MΩ
3	Dielectric Srrength耐壓強度	AC 500V, 0.5Ma, 1分鐘, 相鄰兩導體在空氣中	PASS
4	Continuity Test導通測試	Apply Test DC 3V	No open/Short Citcuit
5	Rated Current 額定電流		0.5A
6	Rated Voltage&Temperature 額定電壓及溫度	UL Sub, 758	60V 105℃
7	Operating Temperature操作溫度	Fixed Wiring Condition	-40℃~105℃
8	Flammability Test耐燃性測試	UL Sub, 758 V W-1	PASS
9	Heat Resistance抗熱測試	85℃ / 96Hrs	No Trouble with insulation Resistance and withstand voltage絕緣電阻與耐電壓符合要求
10	Humidity Resistance抗溼測試	40℃ , 95%RH, 96Hrs	
11	Temperature Cycling Test 溫度循環測試	-40℃ for 4hrs--85℃ for 4hrs--25℃ for 1hrs (5 cyc)	
12	Sliding Test柔性測試	R=Cable thickness	耐曲折測試≥ 30cycle
13		15mmR, 70cycle/min , 25mm往復運動	耐曲折測試≥ 100,000cycle
14	Abrasion Test耐磨測試	Ø5mm, 600g, 60cycle/min	Min 10,000cycles 10,000回以上

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

照片框

ORDER INFORMATION

FPV-CB12-051-LF

SERIES

LEADFREE

51mm

12 WAY

BOTH SIDES

CABLE

DESCRIPTION: