


線材加工圖

加工項目:

1.線外加工:線身包覆鋁箔麥拉如下圖



No. of Conductor	15										
SYMBOL	P	W	SP	M	A	TL	T	S1	S2	S3	S4
RANGE	0.5	8.0	7.0	0.5	0	300	0.3	4	4	6	6
TOLERANCE	±0.05	±0.1	±0.1	±0.1	±0.5	±3	±0.05	±1	±1	±1	±1
CONDUCTOR	Tin Plated Copper		Thickness(Ct)		0.035		±0.005				
SPECIFICATION	Wire (Tin 1~3um)		Width(Cw)		0.3		±0.03				

Note:

UL Style: 20798 80°C 60V

ROSH: YES

Operating Temperature: -40°C~85°C

Dielectric Strength: AC500V / 10ma / 1 min

Rated Current: 0.5A

儲存環境: 16°C~27°C / 濕度 65RH%

Material:

Insulation Film:

Polyester White

Supporting Tape:

Polyester Blue

Conductor:

Tin Plated Flat Copper Wire

EMI對策:

鋁箔麥拉+導電膠

單導鋁箔麥拉結構表示圖



MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±

.X ±

.XX ±

.XXX ±

ANG ±

PPOJECTION

照片框

ORDER INFORMATION

FPV-CT15-300-LF
SERIES | LEADFREE
300mm
15 WAY
BOTH SIDE SHLD
CABLE

DESCRIPTION: 0.5PH 15PIN L=300mm D TYPE +鋁箔