



SPEC :

1. Housing: High-Temp Plastic, UL94-V
Color: Nature (Ivory) (LCP)
2. Contact: Phosphor Bronze (C5191)
3. Solder Tab: BRASS (C2680)

No. of contacts	英稱p數	Dimensions			No. of contacts	英稱p數	Dimensions		
		A	B	C			A	B	C
4	●	8.50	1.50	2.60	26	●	23.00	16.00	17.10
5		9.00	2.00	3.10	27		23.50	16.50	17.60
6	●	9.50	2.50	3.60	28	●	24.00	17.00	18.10
7		10.00	3.00	4.10	29		24.50	17.50	18.60
8	●	10.50	3.50	4.60	30	●	25.00	18.00	19.10
9	●	11.00	4.00	5.10	31		25.50	18.50	19.60
10	●	11.50	4.50	5.60	32	●	26.00	19.00	20.10
11		12.00	5.00	6.10	33		26.50	19.50	20.60
12	●	12.50	5.50	6.60	34		27.00	20.00	21.10
13		13.00	6.00	7.10	35		27.50	20.50	21.60
14	●	13.50	6.50	7.60	36		28.00	21.00	22.10
15		14.00	7.00	8.10	37		28.50	21.50	22.60
16	●	14.50	7.50	8.60	38		29.00	22.00	23.10
17		15.00	8.00	9.10	39		29.50	22.50	23.60
18	●	15.50	8.50	9.60	40	●	30.00	23.00	24.10
19		16.00	9.00	10.10	41		30.50	23.50	24.60
20	●	16.50	9.50	10.60	42	●	31.00	24.00	25.10
21		17.00	10.00	11.10	43		31.50	24.50	25.60
22	●	17.50	10.50	11.60	44	●	32.00	25.00	26.10
23		18.00	11.00	12.10	45	●	32.50	25.50	26.60
24	●	18.50	11.50	12.60	46		33.00	26.00	27.10
25		19.00	12.00	13.10	47		33.50	26.50	27.60
					48	●	34.00	27.00	28.10

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±

PJECTION

照片框

ORDER INFORMATION

FPV-VL2L40-xx-LF
SERIES | | | | | LEADFREE
04-48WAY
HIGH 4.04mm
L TYPE FOOT
DUAL CONTACT
NON ZIF

DESCRIPTION: 0.5PH 4.05H 無蓋有焊立貼單接正腳位

煜倫股份有限公司

www.morethanall.com