










Material:

- 1.1 Housing: thermoplastic high temp. UL94V-0; Color: Natural.
- 1.2 Latch: thermoplastic high temp. UL94V-0; Color: Black.
- 1.3 Terminal: Copper Alloy.
- 1.4 Fitting Nail: Copper Alloy.



PIN NO.	DIM. A	DIM. B	DIM. C	DIM. D
4~N~60	NX0.5+4.40	NX0.5+1.50	NX0.5-0.50	NX0.5+0.60

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.20
.XX ± 0.15
.XXX ± 0.10
ANG ±

照片框

ORDER INFORMATION

FPV-WHB201G-xx-LF

SERIES
90°SMT
GOLD
HIGH 2.0mm
BOTTOM CONTACT
HINGED ZIF
LEADFREE
04~60WAY

DESCRIPTION: 0.5mm ZIF FPC CONNECTOR PIANO TYPE H=2.0