


1.MATERIAL:

2. COPLANARITY 0.1 MM MAX. BASE ON DATUM A

3.TRUE POSITION 0.1 MM MAX. BAES ON DATUM B



PCB PATTERN LAYOUT

Part No.	CKT	Dim A	Dim B	Dim C	Dim D	Dim E
FX8-P11PC-020	20	5.4	8.7	11.0	12.6	10.2
FX8-P11PC-030	30	8.4	11.7	14.0	15.6	13.2
FX8-P11PC-060	60	17.4	20.7	23.0	24.6	22.2
FX8-P11PC-080	80	23.4	26.7	29.0	30.6	28.2
FX8-P11PC-090	90	26.4	29.7	32.0	33.6	31.2
FX8-P11PC-100	100	29.4	32.7	35.0	36.6	34.2
FX8-P11PC-120	120	35.4	38.7	41.0	42.6	40.2
FX8-P11PC-140	140	41.4	44.7	47.0	48.6	46.2
FX8-P11PC-160	160	47.4	50.7	53.0	54.6	52.2



TERMINAL

TOLERANCES ARE

 $X_{\pm}$
$$\lambda \pm \gamma \gamma$$
 $XXX \pm$

NO 1

PPOJECTION 

照片框

FX8-P11PC-xxx-LF

SERIES
CAP
POST
UNMATED HIGH 11mm
PLUG
020-160WAY
LEADFREE

DESCRIPTION: 0.6mm BTB PLUG SMT S/T D/R TYPE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com