

RECOMMENDED P.C.B LAYOUT

A: 6.00 mm B: 3.00 mm C: 1.50 mm

MATERIAL

HOUSING : THERMOPLASTIC UL94V-0

CONTACT : COPPER ALLOYS

SPECIFICATION


CURRENT: 3A

OPERATING TEMPERATURE: -55°C TO $+105^{\circ}\text{C}$

CONTACT RESISTANCE : 20 MILLIOHMS MAX

INSULATION RESISTANCE : 1000 MEGAOHMS MIN

WITHSTANDING VOLTAGE: AC 1000V RMS



RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, $\pm$
.X ± 0.38
.XX ± 0.25
.XXX $\pm$
ANG $\pm 5^{\circ}$

PPOJECTION

照片框

ORDER INFORMATION

H-RL-1X14EL3456912-LF
SERIES 14 WAY
LOW
DIP 90°
EMPTY LEFT 3.4.5.6.9.12
LEADFREE

DESCRIPTION: