

## MATERIAL

Contact Pin : Brass



## SPECIFICATION

Current Rate : 3 AMP


Insulation Resistance : 5000M $\Omega$ Min. at DC 500V

Contact Resistance : 20m $\Omega$ Max. at DC 100mA

Dielectric Voltage : AC 500V for one minute



| POLES | DIM E | POLES | DIM E |
|-------|-------|-------|-------|
|       |       | 21    | 50.80 |
| 2     | 2.54  | 22    | 53.34 |
| 3     | 5.08  | 23    | 55.88 |
| 4     | 7.62  | 24    | 58.42 |
| 5     | 10.16 | 25    | 60.96 |
| 6     | 12.70 | 26    | 63.50 |
| 7     | 15.24 | 27    | 66.04 |
| 8     | 17.78 | 28    | 68.58 |
| 9     | 20.32 | 29    | 71.12 |
| 10    | 22.86 | 30    | 73.66 |
| 11    | 25.40 | 31    | 76.20 |
| 12    | 27.94 | 32    | 78.74 |
| 13    | 30.48 | 33    | 81.28 |
| 14    | 33.02 | 34    | 83.82 |
| 15    | 35.56 | 35    | 86.36 |
| 16    | 38.10 | 36    | 88.90 |
| 17    | 40.64 | 37    | 91.44 |
| 18    | 43.18 | 38    | 93.98 |
| 19    | 45.72 | 39    | 96.52 |
| 20    | 48.26 | 40    | 99.06 |



Recommended P.C.B Layout

照片框

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
PCB CONNECTORS  
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X<sub>s</sub> ±  
.X ± 0.30  
.XX ± 0.20  
.XXX ±  
ANG ±



## ORDER INFORMATION

H-RLT-1Xxx-LF  
SERIES | LEADFREE  
1X02:02WAY  
1X40:40WAY  
TIN  
LOW  
DIP 90°

DESCRIPTION: PIN HEADER 2.54\*2.54mm RIGHT ANGLE TYPE, SINGLE ROW