



RECOMMENDED P. C. B LAYOUT

CONTACTS	1X26
1X2	1X27
1X3	1X28
1X4	1X29
1X5	1X30
1X6	1X31
1X7	1X32
1X8	1X33
1X9	1X34
1X10	1X35
1X11	1X36
1X12	1X37
1X13	1X38
1X14	1X39
1X15	1X40
1X16	1X41
1X17	1X42
1X18	1X43
1X19	1X44
1X20	1X45
1X21	1X46
1X22	1X47
1X23	1X48
1X24	1X49
1X25	1X50

1.00 x (CONTACTS-1) ± 0.20



MATERIAL

HOUSING : NYLON 6T,UL94V-0  
 CONTACT : COPPER ALLOYS  
 PLATED : GOLD-FLASH  
 COLOR : BLACK

SPECIFICATION

CURRENT : 1A  
 OPERATING TEMPERATURE : -55°C TO +105°C  
 CONTACT RESISTANCE : 20 MILLIOHMS MAX  
 INSULATION RESISTANCE : 500 MEGAOHMS MIN  
 WITHSTANDING VOLTAGE : 200V AC MIN

A: 3.00 mm B: 2.50 mm C: 1.35 mm

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

X. ±  
 .X ± 0.38  
 .XX ± 0.25  
 .XXX ±  
 ANG ± 5°

PJECTION

照片框

ORDER INFORMATION

H10-R10133025-1Xxx-LF  
 SERIES | | | | LEADFREE  
 | | | | 1X02:02WAY  
 | | | | 1X50:50WAY  
 DIP 90° | | | | DIP 2.5mm  
 BASE 1.0mm | | | | CONTACT 3.0mm  
 | | | | R/A 1.35mm

DESCRIPTION: