



PC BOARD LAYOUT

- Note:
1. Material:
 - 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
 - 1.2 Contact: Copper alloy,t=0.20mm
 - 1.3 Shell: Spcc,t=0.30mm
 2. Specification:
 - 2.1 Current rating: 1 A Max.
 - 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
 - 2.3 Contact resistance: 30 OHM Max.
 - 2.4 Insulation resistance: 1000 OHM Min.
 - 2.5 Total mating force: 8.0 Kgf Max.
 - 2.6 Total unmating force: 1.5 Kgf Min.
 - 2.7 Temperature range: -55°C-85°C

PART NO	A±0.25	B±0.20	C±0.20	D±0.20	E±0.30	F±0.25	G±0.25	H±0.05	I ±0.20		
HDD-SGJ-15	30.81	24.99	16.33	7.9	16.0		12.55	2.29	3.96		
HDD-SGJ-26	39.25	33.32	24.66	7.9	16.0		12.55	2.29	3.96		
HDD-SGJ-44	53.04	47.04	38.38	7.9	16.0		12.55	2.29	3.96		
HDD-SGJ-62	69.50	63.50	54.84	7.9	16.0		12.55	2.41	3.96		

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司
www.morethanall.com

DRAWING BY CY
CHECKED BY GENIUS
UNIT / mm SCALE 1 : 1
DATE
SIZE A4 PPROJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ± 0.10
ANG ±



ORDER INFORMATION

HDD-SGJ-xx-LF
SERIES | LEADFREE
| 15-62WAY
| JACKSCREW
| FULL GOLD
| FEMALE

DESCRIPTION: HIDDEN D-SUB 前鉗型 (不通孔)