



规格:

1. 插入力: 44.1N MAX.
2. 拔出力: 9.8N MIN. 39.2N MAX
3. 耐久性: 10000 CYCLES . AT100±50 CYCLES PER HOUR
4. 额定电流: 0.5A MIN
5. 额定电压: 40V MAX
6. 耐电压: 500V AC MIN. (UNMATED) 300V AC MIN. (MATED)
7. 接触阻抗: 30mΩ MAX. 壳体50mΩ MAX
8. 绝缘电阻: 100MΩ MIN (UNMATED) 10MΩ MIN (MATED)
9. 工作温度: 0°C TO 50°C
10. 所用材质须符合RoHS要求

○ 后塞	1PCS	LCP+30%GF(黑色), UL94-V0
○ 胶芯	1PCS	
○ 壳体	1PCS	c2680/spcc, T=0.50±0.02, 表面镀镍100u"或镀金G/F
○ 10PIN 端子	10PCS	铜材C5191(HV180-210), T=0.25±0.01
○ 9PIN 端子	9PCS	
零件	数量	材料规格

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

P PROJECTION

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ± 0.10
ANG ± 1°

照片框

ORDER INFORMATION

HDMI-SE-19-LF
SERIES | LEADFREE
19 WAY
EDGE CLIP
FEMALE

DESCRIPTION: HDMI A TYPE F 夹板式