



Note:

1. Material:
 - 1.1 Insulator: High temperature thermoplastic with g.f,UL94v-0
 - 1.2 Contact: Copper alloy,t=0.20mm
 - 1.3 Shell: Spcc,t=0.30mm
2. Specification:
 - 2.1 Current rating: 1 A Max.
 - 2.2 Dielectric withstanding voltage: 750 V(ac) for 1 min.
 - 2.3 Contact resistance: 30 mΩ Max.
 - 2.4 Insulation resistance: 1000 MΩ Min.
 - 2.5 Total mating force: 8.0 Kgf Max.
 - 2.6 Total unmating force: 1.5 Kgf Min.
 - 2.7 Temperature range: -55°C~85°C

8	Back-shell			
7	Front-shell			
6	Clip			No finish
5	Contact			Selective Au plated on mating area
4	Contact			
3	Contact			
2	Contact			
1	Housing			Black
No.	Name	Q'ty	Part No.	Finish

PART NO.	A ± 0.2	B ± 0.2	C ± 0.2	D ± 0.2	E ± 0.2
HDR-SS-15	30.81	24.99	16.33	7.90	12.55
HDR-SS-26	39.25	33.32	24.66	7.90	12.55
HDR-SS-44	53.04	47.04	38.38	7.90	12.55
HDR-SS-62	69.32	63.50	54.84	7.90	12.55

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4 PPROJECTION

- X, ±
- .X ±
- .XX ±
- .XXX ±
- ANG ±

照片框

ORDER INFORMATION

HDR-SS-15-LF
SERIES | LEADFREE
15 WAY
SEMI GOLD
FEMALE

DESCRIPTION:

煜倫股份有限公司

www.morethanall.com