



MATERIAL:

INSULATOR : PBT+30% GLASS FIBER (UL 94V-0) BLACK.
 CONTACT MATERIAL : BRASS OR PHOSPHOR BRONZE.
 CONTACT FINISH : GOLD OVER NICKEL.
 SHELL FINISH : STEEL NICKEL PLATED.

SPECIFICATION:

CURRENT RATING : 2 AMP
 DIELECTRIC WITHSTANDING VOLTAGE : 1000V PER MINUTE.
 INSULATION RESISTANCE : 1000MΩ MIN. AT 500V DC.
 CONTACT RESISTANCE : 15mΩ MAX. 10 SEC.
 OPERATING TEMPERATURE : -55°C ~ +105°C.

CONTACTS	Dim A ± 0.20	Dim B ± 0.25	Dim C ± 0.38	Dim D	Dim E	Dim F
15 pin	16.33	24.99	30.80	2.29	0.25	0.89
26 pin	24.66	33.32	39.10	2.29	0.51	0.64
44 pin	38.38	47.04	53.00	2.29	0.51	0.64
62 pin	54.84	63.50	69.32	2.41	0.58	0.62

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
 .X ± 0.25
 .XX ± 0.15
 .XXX ± 0.05
 ANG ±

照片框

ORDER INFORMATION

HDRF-SGN-xx-LF
 SERIES | | | LEADFREE
 | | | 15-62 WAY
 | | | NUT
 | | | GOLD
 | | | FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: HIGH DENSITY D-SUB CONNECTORS RIGHT ANGLE, EMI FEMALE FOOTPRINT : 8.89mm