



PIN OUT:

P1		P2
1	_____	1
2	_____	2
3	_____	3
	⋈	⋈
76	_____	76
77	_____	77
78	_____	78
shell	_____	shell

ITEM	PART NO.	DESCRIPTION	REMARK
1	HDS-PS-78	D-SUB 78P Male High Density SolderType Connector	1
2	HDS-SS-78	D-SUB 78P Female High Density SolderType Connector	1
3	808-4.0*45B	#4*40 45B Screw	4
4	810A-78C28A15.0BK	UL 2464 28awg*78C+ae Color: Black	
5	827-PVC-50P-BK	Pvc Molding 50p Color Black	

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

HDX2-787828-E2M-LF

SERIES

LEADFREE

2000mm

MALE TO FEMALE

28 AWG

78 TO 78 WAY

DESCRIPTION: ROUND CABLE