



PCB Layout

• MATERIALS:(RoHS Compliant)

Housing And Cover: Plastic Thermoplastic P.B.T UL94V-0 Black  
 Contacts: Phosphor Bronze Gold Selective Plated  
 Front Shell: Steel Nickel Plated Over Copper  
 Bracket: Steel Nickel Plated Over Copper  
 Boardlock: Brass Tin Plated Over Copper

• ELECTRICAL CHARACTERISTICS:

Contact Current Rating: 0.5 Amp  
 Dielectric Withstanding Voltage: 500V AC  
 Insulation Resistance: >500MΩ/Min  
 Contact Resistance: 35mΩ/Max  
 Operation Temperature: -55°C ~ +85°C

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE

SIZE A4

X, ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

PPOJECTION

照片框

ORDER INFORMATION

HPC-SRL-100-LF  
 SERIES | LEADFREE  
 | 100 WAY  
 | LOCK  
 | DIP 90°  
 | FEMALE

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 1.27mm (.050") Ribbon 100Pos Receptacles Headers Right-Angle Mount Type