

RECOMMENDED P.C.B. LAYOUT  
INSPECTION DIMENSION:(A)~(J)

NOTES

- MATERIAL:  
Housing:PBT, UL 94V-0, Color:Black.  
Terminal:Copper Alloy.  
Shell:Zinc Alloy.  
Boardlock:Copper Alloy.
- FINISH:  
Terminal:Gold Plated over Nickel at Contact Area.  
Tin Plated over Nickel at Solder Area.  
Shell:Nickel Plated.  
Boardlock:Tin Plated.
- This Product is LEAD-FREE & RoHS Compliance Product.

SPECIFICATIONS

- SCSI
  - Current Rating: 1 Ampere per Contact
  - Contact Resistance: 35 Milliohms Max.
  - Insulation Resistance: 1000 Megohms Min.
  - Dielectric Withstanding Voltage: 500 VAC(RMS)
  - Total Mating Force: 23.8 Kgf Max.
  - Total Unmating Force: 2.0 Kgf Min.
  - Operating Temperature: -55°C to +85°C

RoHS Compliant

TOLERANCES ARE



DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm SCALE 1 : 1

DATE


SIZE A4

- X, ±
- .X ±
- .XX ± 0.25
- .XXX ± 0.13
- ANG ± 2°



照片框

ORDER INFORMATION



DESCRIPTION:

煜倫股份有限公司

www.morethanall.com