



Specifications:

Current Rating:1.0 Amp

Contact resistance:30m Ohm Max. at 6V DC 0.3A

Insulator resistance:1000M ohm min. at 500V DC

Withstanding Voltage:500V AC/Minute

Operating Temperature Range:-40°~+105°C

Flat ribbon cable with 0.635mm pitch.

Material And Finish

Insulator:PBT&Glass-fiber reinforced UL94V-0

Insulator Color:Black

Contact:Phosphor Bronze

Contact Plating:See Contact Plating Tab.

Note:(*)Marked is Important DIM For QC.

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

TOLERANCES ARE

X. ±
.X ± 0.35
.XX ± 0.25
.XXX ± 0.10
ANG ±

PPOJECTION

照片框

ORDER INFORMATION

HPDP-PFS3-068-LF
SERIES
LEADFREE
68 WAY
THREE TYPE
IDC 0.635mm
MALE

DESCRIPTION: 1.27mm Pitch SCSI-III Male IDC Type Series