



Recommended P.C.B Layout

MATERIAL
 Insulator : NY6T
 Contact Pin : Brass

SPECIFICATION

Current Rate : 3 AMP
 Insulation Resistance : 5000MΩMin. at DC 500V
 Contact Resistance : 20mΩMax. at DC 100mA
 Dielectric Voltage : AC 500V for one minute
 Operating Temperature: -40°C to +105°C

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X, ±
 .X ± 0.30
 .XX ± 0.20
 .XXX ±
 ANG ± 3°

PJECTION

照片框

ORDER INFORMATION

HSB-D3706060-1X15EM2-LF
 SERIES | | | | | LEADFREE
 | | | | | EMPTY 2.3 PIN
 | | | | | 15 WAY
 | | | | | DIP 6.0mm
 DIP180° | | | | | CONTACT 6.0mm
 | | | | | TOTAL 37.0mm

DESCRIPTION: PIN HEADER 2.54*2.54mm STRAIGHT TYPE, SINGLE ROW OPPOSITE INSULATORS