






NOTES

1.MATERIAL

1.1 Insulator: P.B.T+15% G.F(UL94V-0)

1.2 Contact: Phosphor Bronze

2.SPECIFICATION

2.1 Current Rating: 1 Amp

2.2 Current Voltage: 30V RMS Max

2.3 Dielectric Withstanding: AC 500V min Per minute

2.4 Insulation Resistance: 500M ohms min At
DC 500V

2.5 Contact Resistance: 20m ohms Max

2.6 Operating Temperature: -45°C ~ 105°C

2.7 Insertion force: 0.5KgF/pin MAX.

2.8 Withdrawal force: 0.1KgF/pin MIN.

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.38
.XX ± 0.25
.XXX ± 0.15
ANG ± 2°



ORDER INFORMATION

J-B-04-LF
SERIES | LEADFREE
HIGH 4.5mm
OPEN TYPE

DESCRIPTION: MJ 4.5B黑磷銅半面金 RoHS