

DIP TYPE

■ MATERIAL

INSULATOR: PBT +30% GLASS FIBER (UL94V-0).
 CONTACT: PHOSPHOR BRONZE OR BRASS.
 PLATING: GOLD OVER NICKEL.

■ SPECIFICATION

CURRENT RATING: 3 AMP.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 VOLTAGE : 500V FOR ONE MINUTE.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +105°C.

| Circuit | Dimension | | | | | Circuit | Dimension | | | | |
|---------|-----------|--------|--------|--------|--------|---------|-----------|--------|--------|--------|--------|
| | A | B | C | D | E | | A | B | C | D | E |
| 05 | 15.84 | 24.06 | 27.40 | 34.94 | 41.24 | 32 | 122.76 | 130.98 | 134.32 | 141.86 | 148.16 |
| 06 | 19.80 | 28.02 | 31.36 | 38.90 | 45.20 | 35 | 134.64 | 142.86 | 146.20 | 153.74 | 160.04 |
| 08 | 27.72 | 35.94 | 39.28 | 46.82 | 53.12 | 36 | 138.60 | 146.82 | 150.16 | 157.70 | 164.00 |
| 10 | 35.64 | 43.86 | 47.20 | 54.74 | 61.04 | 43 | 166.32 | 174.54 | 177.88 | 185.49 | 191.48 |
| 11 | 39.60 | 47.82 | 51.16 | 58.70 | 65.00 | | | | | | |
| 12 | 43.56 | 51.78 | 55.12 | 62.66 | 68.96 | | | | | | |
| 14 | 51.48 | 59.70 | 63.04 | 70.58 | 76.88 | | | | | | |
| 15 | 55.44 | 63.66 | 67.00 | 74.54 | 80.84 | | | | | | |
| 16 | 59.40 | 67.62 | 70.96 | 78.50 | 84.80 | | | | | | |
| 18 | 67.32 | 75.54 | 78.88 | 86.42 | 92.72 | | | | | | |
| 20 | 75.24 | 83.46 | 86.80 | 94.34 | 100.64 | | | | | | |
| 22 | 83.16 | 91.38 | 94.72 | 102.26 | 108.56 | | | | | | |
| 23 | 87.12 | 95.34 | 98.68 | 106.22 | 112.52 | | | | | | |
| 25 | 95.04 | 103.26 | 106.60 | 114.14 | 120.44 | | | | | | |
| 28 | 106.92 | 115.14 | 118.48 | 126.02 | 132.32 | | | | | | |
| 30 | 114.84 | 123.06 | 126.40 | 133.94 | 140.24 | | | | | | |
| 31 | 118.80 | 127.02 | 130.36 | 137.90 | 144.20 | | | | | | |



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1


DATE

SIZE A4

TOLERANCES ARE

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

PJECTION



ORDER INFORMATION



DESCRIPTION: 3.96 PITCH SINGLE ROW WITH MOUNTING EAR