






DIP TYPE



MATERIAL

INSULATOR: PBT +30% GLASS FIBER (UL94V-0).

CONTACT: BRASS

PLATING: GOLD OVER NICKEL.

SPECIFICATION

CURRENT RATING: 3 AMP.

INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.

CONTACT RESISTANCE: 20 MILLIOHMS MAX.

VOLTAGE : 500V FOR ONE MINUTE.

ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +125°C.

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
10	15.84	24.06	27.40	64	122.76	130.98	134.32
12	19.80	28.02	31.36	70	134.64	142.86	146.20
16	27.72	35.94	39.28	72	138.60	146.82	150.16
20	35.64	43.86	47.20				
24	43.56	51.78	55.12				
26	47.52	55.74	59.08				
28	51.48	59.70	63.04				
30	55.44	63.66	67.00				
32	59.40	67.62	70.96				
36	67.32	75.54	78.88				
40	75.24	83.46	86.80				
44	83.16	91.38	94.72				
46	87.12	95.34	98.68				
50	95.04	103.26	106.60				
56	106.92	115.14	118.48				
60	114.84	123.06	126.40				
62	118.80	127.02	130.36				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X. ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

KE-DXE5-xx-LF
SERIES
LEADFREE
10~72 WAY
ROW PITCH 5.08mm
NON EAR
DIP 180°

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAP