


DIP TYPE



- MATERIAL
 INSULATOR: PBT +30% GLASS FIBER (UL94V-0).
 CONTACT: PHOSPHOR BRONZE OR BRASS.
 PLATING: GOLD OVER NICKEL.

- SPECIFICATION
 CURRENT RATING: 3 AMP.
 INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
 CONTACT RESISTANCE: 20 MILLIOHMS MAX.
 VOLTAGE : 500V FOR ONE MINUTE.

- ENVIRONMENTAL
 TEMPERATURE RANGE: -40°C TO +105°C.

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
5	15.84	24.06	27.40	32	122.76	130.98	134.32
6	19.80	28.02	31.36	35	134.64	142.86	146.20
8	27.72	35.94	39.28	36	138.60	146.82	150.16
10	35.64	43.86	47.20				
12	43.56	51.78	55.12				
13	47.52	55.74	59.08				
14	51.48	59.70	63.04				
15	55.44	63.66	67.00				
16	59.40	67.62	70.96				
18	67.32	75.54	78.88				
20	75.24	83.46	86.80				
22	83.16	91.38	94.72				
23	87.12	95.34	98.68				
25	95.04	103.26	106.60				
28	106.92	115.14	118.48				
30	114.84	123.06	126.40				
31	118.80	127.02	130.36				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT/mm SCALE 1:1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

KE-DXEBK-1Xxx-LF
 SERIES | LEADFREE
 | 1X05:05WAY
 | 1X36:36WAY
 | BLACK
 | NON EARS
 | DIP 180°

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAR