






SOLDER TYPE



- MATERIAL
INSULATOR: PBT +30% GLASS FIBER (UL94V-0).
CONTACT: PHOSPHOR BRONZE OR BRASS.
PLATING: GOLD OVER NICKEL.

- SPECIFICATION
CURRENT RATING: 3 AMP.
INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.
CONTACT RESISTANCE: 20 MILLIOHMS MAX.
VOLTAGE : 500V FOR ONE MINUTE.

- ENVIRONMENTAL
TEMPERATURE RANGE: -40°C TO +105°C.

Circuit	Dimension			Circuit	Dimension		
	A	B	C		A	B	C
5	15.84	24.06	27.40	32	122.76	130.98	134.32
6	19.80	28.02	31.36	35	134.64	142.86	146.20
8	27.72	35.94	39.28	36	138.60	146.82	150.16
10	35.64	43.86	47.20				
12	43.56	51.78	55.12				
13	47.52	55.74	59.08				
14	51.48	59.70	63.04				
15	55.44	63.66	67.00				
16	59.40	67.62	70.96				
18	67.32	75.54	78.88				
20	75.24	83.46	86.80				
22	83.16	91.38	94.72				
23	87.12	95.34	98.68				
25	95.04	103.26	106.60				
28	106.92	115.14	118.48				
30	114.84	123.06	126.40				
31	118.80	127.02	130.36				

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

KE-SXEBK-1Xxx-LF
SERIES LEADFREE
1X05:05 WAY
1X36:36 WAY
BLACK
NON EARS
SOLDER

DESCRIPTION: 3.96 PITCH WITH OUT MOUNTING EAR