



■ MATERIAL

INSULATOR: PBT +30% GLASS FIBER (UL94V-0).

CONTACT: PHOSPHOR BRONZE OR BRASS.

PLATING: GOLD OVER NICKEL.

■ SPECIFICATION

CURRENT RATING: 3 AMP.

INSULATION RESISTANCE: 5000 MEGOHMS MIN AT 500 VDC.

CONTACT RESISTANCE: 20 MILLIOHMS MAX.

VOLTAGE : 500V FOR ONE MINUTE.

■ ENVIRONMENTAL

TEMPERATURE RANGE: -40°C TO +105°C.

Circuit	Dimension					Circuit	Dimension				
	A	B	C	D	E		A	B	C	D	E
10	15.84	24.06	27.40	34.94	41.24	64	122.76	130.98	134.32	141.86	148.16
12	19.80	28.02	31.36	38.90	45.20	70	134.64	142.86	146.20	153.74	160.04
16	27.72	35.94	39.28	46.82	53.12	72	138.60	146.82	150.16	157.70	164.00
20	35.64	43.86	47.20	54.74	61.04	86	166.32	174.54	177.88	185.49	191.48
22	39.60	47.82	51.16	58.70	65.00						
24	43.56	51.78	55.12	62.66	68.96						
28	51.48	59.70	63.04	70.58	76.88						
30	55.44	63.66	67.00	74.54	80.84						
32	59.40	67.62	70.96	78.50	84.80						
36	67.32	75.54	78.88	86.42	92.72						
40	75.24	83.46	86.80	94.34	100.64						
44	83.16	91.38	94.72	102.26	108.56						
46	87.12	95.34	98.68	106.22	112.52						
50	95.04	103.26	106.60	114.14	120.44						
56	106.92	115.14	118.48	126.02	132.32						
60	114.84	123.06	126.40	133.94	140.24						
62	118.80	127.02	130.36	137.90	144.20						

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ±
.XX ±
.XXX ±
ANG ±

照片框

ORDER INFORMATION

KE-YLE-xx-LF
SERIES | LEADFREE
10~86WAY
LOW EARS
Y TYPE

DESCRIPTION: 3.96 PITCH WITH MOUNTING EAR STRADDLE PIN TYPE