



MATERIAL: NYLON 66.UL94V-2  
 CURRENT RATING: 7A  
 VOLTAGE RATING: 250V/AC

CIRCUITS	PART NO	DIMENSION	
		A	B
2	KK-HX-02	3.96	8.62
3	KK-HX-03	7.92	12.58
4	KK-HX-04	11.88	16.54
5	KK-HX-05	15.84	20.50
6	KK-HX-06	19.80	24.46
7	KK-HX-07	23.76	28.42
8	KK-HX-08	27.72	32.38
9	KK-HX-09	31.68	36.34
10	KK-HX-10	35.64	40.30
11	KK-HX-11	39.60	44.26
12	KK-HX-12	43.56	48.22
13	KK-HX-13	47.52	52.18
14	KK-HX-14	51.48	56.14
15	KK-HX-15	55.44	60.10
16	KK-HX-16	59.40	64.06
17	KK-HX-17	63.36	68.02
18	KK-HX-18	67.32	71.98
19	KK-HX-19	71.28	75.94
20	KK-HX-20	75.24	79.90

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PPOJECTION

X. ±  
 .X ±  
 .XX ±  
 .XXX ±  
 ANG ±

照片框

ORDER INFORMATION

KK-HX-xx-LF  
 SERIES | LEADFREE  
 | 02-20WAY  
 | W/O POLARIZING RIB  
 HOUSING

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: 3.96mmCONNECTOR HOUSING