



MATERIAL: NYLON 66.UL94V-2  
 CURRENT RATING: 7A  
 VOLTAGE RATING: 250V/AC

CIRCUITS	PART NO	DIMENSION	
		A	B
2	KK-RV-02	3.96	7.92
3	KK-RV-03	7.92	11.88
4	KK-RV-04	11.88	15.84
5	KK-RV-05	15.84	19.80
6	KK-RV-06	19.80	23.76
7	KK-RV-07	23.76	27.72
8	KK-RV-08	27.72	31.68
9	KK-RV-09	31.68	35.64
10	KK-RV-10	35.64	39.60
11	KK-RV-11	39.60	43.56
12	KK-RV-12	43.56	47.52
13	KK-RV-13	47.52	51.48
14	KK-RV-14	51.48	55.44
15	KK-RV-15	55.44	59.40
16	KK-RV-16	59.40	63.36
17	KK-RV-17	63.36	67.32
18	KK-RV-18	67.32	71.28
19	KK-RV-19	71.28	75.24
20	KK-RV-20	75.24	79.20

RoHS Compliant

TOLERANCES ARE

**MORETHANALL**  
 PCB CONNECTORS  
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1:1

DATE

SIZE A4

PJECTION

X.±  
 .X±  
 .XX±  
 .XXX±  
 ANG±

照片框

ORDER INFORMATION

KK-RV-xx-LF  
 SERIES | LEADFREE  
 | 02-20WAY  
 | REVERSED  
 | DIP 90°

DESCRIPTION: 3.96mm CONNECTOR WAFER