

FEATURE:
 INSULATOR
 Glass-Filled P.B.T. is 94V-0 rated
CONTACT
 Phosphor Bronze selective gold plating over nickel
SPECIFICATION:
 Current Rating: 3 amperes
 Contact Resistance: 21 miniohms max.
 Operation Temperature: -55°C to 105°C
 Voltage Rating: 810 VAC 1 minute
 Insulation Resistance: 5100 megohms min
 Insertion Force: 412 grams max. per pair
 Withdrawal Force: 32 grams min. per pair

KSL-DME19-xxx-LF
LEADFREE

RoHS Compliant

CONTACTS NO	DIM A	DIM B	DIM C	DIM D	DIM E
18/36	93.12	86.62	79.02	75.72	67.32
20/41	100.94	94.54	86.94	83.64	75.24
22/44	108.86	102.46	94.86	91.56	83.16
28/56	132.62	126.22	118.62	115.32	106.92
31/60	140.54	134.14	126.54	123.24	114.84
43/86	192.02	185.62	178.02	174.72	166.32
50/100	219.74	213.34	215.74	212.44	194.14


MORETHANALL
 CONNECTORS
 ASSEMBLIES

PART NO. **KSL-DME19-xxx**

DWG NO. **KSL-DME19-xxx**

FILE NO.


UNIT / mm

SCALE 1:1

CHECKED BY CY

DRAWING BY

PROJECTION



TOLERANCES ARE

$.X \pm 0.2$
 $.XX \pm$
 $.XXX \pm$
 AWG

DESCRIP TION:

EDGE CONNECTOR 3.96mm PITCH
WITH MID-HIGH MOUNTING EARS

AREA

REVISIONS

HK

DATE

煜倫股份有限公司