

FEATURE:

INSULATOR

Glass-Filled PBT is 94V-0 rated, Color : BLACK

CONTACT

Phosphor Bronze selective gold plating over nickel

SPECIFICATION:

Current Rating : 3 Amperes

Contact Resistance : 10 Miniohms Maximum.

Operation Temperature : -55°C to +105°C

Voltage Rating : 1800 VAC 1 Minute

Insulation Resistance : 5000 Megaohms Minimum

Daughter Board Insertion Force : 0.45 kgs Maximum per pair

Daughter Board Withdrawal Force : 0.028 kgs Minimum per pair

Contact tail Insertion into Hole : 40 lbs Maximum

Contact tail Retention In Hole : 10 lbs Minimum

| CONTACTS NO. | DIM A | DIM B | DIM C |
|--------------|--------|--------|--------|
| 28/56 | 118.30 | 115.20 | 106.92 |
| 30/60 | 126.22 | 123.12 | 114.84 |
| 36/72 | 149.98 | 146.88 | 138.60 |
| 40/80 | 165.82 | 162.72 | 154.44 |
| 43/86 | 177.70 | 174.60 | 166.32 |
| 50/100 | 205.42 | 202.32 | 194.04 |

Recommended PCB Hole

Drilled Hole : 1.15±0.03mm

Copper Plate 0.025mm Minimum thickness followed

be Tin/Lead plate to provide finished hole 1.02+0.08mm diameter



煜倫股份有限公司

www.morethanall.com

RoHS Compliant

DRAWING BY CY

CHECKED BY GENIUS

UNIT/ mm SCALE 1:1

DATE

SIZE A4


TOLERANCES ARE

X. ±
 .X ± 0.38
 .XX ± 0.15
 .XXX ± 0.10
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION



DESCRIPTION: PITCH 3.96mm EDGE CARD CONN. PRESS FIT TYPE