




Features:

- ① • 2 ~ 20 circuits available
- Housing material: UL 94V-2 nylon 66
 - Terminal material: Tin-plated phosphor bronze
 - With or without locking ramp and polarizing tabs
 - Feed-Thru and Closed End type
- ② • Wire range: AWG #18 ~ #24 (Flat ribbon wire)

Specification:

- Current rating: 7A AC, DC
 - Voltage rating: 250V AC Max.
 - Contact resistance: Initial value/10m Ω Max.
After environmental testing/20m Ω Max.
 - Insulation resistance: 1000M Ω Min.
 - Dielectric withstanding voltage: 1500V AC/minute
 - Ambient temperature range: -40°C ~ 105°C
- (Including temperature rise)

C	Color	Wire size
3	Orange	#18
4	Yellow	#20
2	Red	#22
9	White	#24



Dimensional Information (mm)

Circuits	Dim. A	Dim. B	Circuits	Dim. A	Dim. B
2	3.96±0.10	7.92	12	43.56±0.25	47.52
3	7.92±0.15	11.88	13	47.52±0.30	51.48
4	11.88±0.15	15.84	14	51.48±0.30	55.44
5	15.84±0.15	19.80	15	55.44±0.30	59.40
6	19.80±0.20	23.76	16	59.40±0.30	63.36
7	23.76±0.20	27.72	17	63.36±0.30	67.32
8	27.72±0.20	31.68	18	67.32±0.35	71.28
9	31.68±0.20	35.64	19	71.28±0.35	75.24
10	35.64±0.25	39.60	20	75.24±0.35	79.20
11	39.60±0.25	43.56			

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES
煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

PPOJECTION

X, ±
.X ± 0.40
.XX ± 0.25
.XXX ± 0.08
ANG ± 1°

照片框

ORDER INFORMATION

KT-HLxxT-xx-LF
SERIES LEADFREE
02~20WAY
TAB
18~24AWG
CLOSED END
HOUSING

DESCRIPTION: