



PCB Layout

Specifications:

Current Rating:7.0A AC/DC
 Voltage Rating:250V AC/DC
 Contact Resistance:10m ohm.Max.
 Insulation Resistance:1,000M ohm.Min.
 Withstanding Voltage:1,500V AC/Minute
 Operating Temperature Range:-40°C To +105°C
 Materials and Finish:
 Insulator:PBT (UL94V-0)
 Insulator Color:Black
 Contact:Brass
 Plating:Tin Plated

RoHS Compliant

TOLERANCES ARE

MORETHANALL
 PCB CONNECTORS
 Cable ASSEMBLIES

煜倫股份有限公司

www.morethanall.com

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm

SCALE 1 : 1

DATE

SIZE A4

X. ±
 .X ±
 .XX ±
 .XXX ±
 ANG ±

P PROJECTION

照片框

ORDER INFORMATION

KX-RL323514030-4X03-LF
 SERIES | | | | | LEADFREE
 DIP 90° | | | | | 12 WAY
 LOW | | | | | R/A 3.53mm | | | | | DIP 3.0mm
 | | | | | BASE 3.2mm | | | | | CONTACT 14.0mm

DESCRIPTION: 3.96mm Wafer R/A Type Four Row