

Recommended P.C.B Layout

MATERIAL

Contact Pin : Brass

SPECIFICATION

Current Rate : 1 AMP

Dielectric voltage: 500V AC for one minute

Insulation Resistance : 1000MΩMin.

Contact Resistance : 10mΩMax.

No. of pins	A	B	C	D
10	31.87	21.70	10.16	17.90
14	36.95	26.88	15.24	22.95
16	39.48	29.27	17.78	25.50
20	44.62	34.50	22.86	30.58
24	49.67	39.50	27.94	35.70
26	52.23	42.05	30.48	38.25
30	57.30	47.20	35.56	43.35
34	62.38	52.15	40.64	48.40
40	69.95	59.90	48.26	56.05
50	82.70	72.55	60.96	68.70
60	95.45	85.25	73.66	81.50
64	100.60	90.35	78.74	86.40

RoHS Compliant

TOLERANCES ARE

MORETHANALL
PCB CONNECTORS
Cable ASSEMBLIES

DRAWING BY CY

CHECKED BY GENIUS

UNIT / mm


SCALE 1 : 1

DATE

SIZE A4

PJECTION

X, ±
.X ± 0.30
.XX ± 0.20
.XXX ±
ANG ± 3°



ORDER INFORMATION

L-R-xx-LF
SERIES | LEADFREE
10-64 WAY
DIP90°

煜倫股份有限公司

www.morethanall.com

DESCRIPTION: